



Type	57658	Safety Features	Wrong cell (alkaline) detection Wrong polarity detection (mechanical) Short circuit detection Low input voltage detection
Designation	Universal Charger	Housing Material	ABS
System to charge	NiMH (Nickel Metal Hydride)	Housing colour	White/Light Grey
Cell sizes	AAA, AA, C, D, 9V	Dimensions	Charger:
Cell configuration	2/4 cells (pairwise) AAA, AA, C, D or 1x 9V	Length	128.5 ± 1 mm
Input	5V = 1000mA 5W	Width	153.5 ± 1 mm
AC-Plug	USB C Plug (50cm USB A to USB C cable included)	Height	48.7 ± 1mm
Charging currents	2/4 x AA/C/D: 450mA; 2/4 x AAA: 200mA; 1x 9V: 35mA	Weight	245 ± 3g
Trickle charge current	60mA (AAA/AA/C/D)		
Cut off Timer	8.5h ± 0.2h (AAA/AA/C/D) / 8.0h ± 0.2h (9V)		
Charge Termination	-dV cut off (AAA/AA/C/D)		
Charge Indicator	green LED		
charging	blinking slow		
defective/wrong cell	blinking fast		
charging complete	solid green		

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries