



Designation:	18631 101 401/18631 201 401
Input:	DC 5V, 250mA – 350mA
Battery Requirement:	1 x 600mAh 3.7V Li_Polymer battery (3.7V 60mAh 2.22Wh battery)
Lamp required:	1pcs LG H35C1 3W 6500k cool white LED
Luminous intensity:	High: 300 lumens or 2080 cd Low: 10 lumens or 72 cd
Range:	91m High / 16m Low <small>(calculated distance at maximum luminous intensity with an illuminance of 0.25 lux)</small>
Weight:	47g (with headstrap)
Material:	PMMA ABS: PA66 <small>All contact parts made of bronze or nickel plated steel</small>
Dimensions:	A: 48.5 mm B: 41 mm C: 40.2 mm
Run Time:	High 1.5 hours (with fully charged) Low: 21 hours (with fully charged) Charging time: ≤3.5 hrs

Features (Technical):

Super bright 3W LG LED

Ratcheted pivot provides stable headlight rotation 120° (6 positions :0, 24°, 48°, 72°, 108°, 120°)

MCU control push switch: Controlled by single On/Off switch

- Short press – On/Off
- Long press while ON – Dimming
- Long press for 2 seconds when Off – Switch Lockout Mode
- Fully Charged: Green indicator LED, constant on
- Indicator LED remains ON while connected to powered micro USB cable
- Indicator LED remains ON while connected to powered micro USB cable
- Indicator LEDs turn off if micro USB cable is disconnected from flashlight or the power source

Battery Indication, 3status: High: Green / Medium: Yellow / Low: Red

- 3.6v-4.2v Green on (40-100% batt capacity)
- 3.3v-3.6v Yellow on (15-40% batt capacity)
- 3.0v-3.3v Red on (0-15% low battery) - remind user to charge

Mounting Clip Assesory & Including USB charging cable

Port cover protects Micro-USB port from environment

Charge every six months

1meter drop test

IPX4 water resistant

Eye risk group 2

10,000 Switch cycle life / 10,000 micro USB Plug Insertion Life Test

10,000 micro USB Plug Insertion Life Test

Passed extreme temperature shock test

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries