



| | | | |
|---------------------------------|---|--|--|
| Type | 16607 101 421 | Features (Technical) | |
| Designation | Aluminium Light F20 Pro | Super bright OSRAM cool white LED | |
| Battery required | 2x AA Alkaline battery | Convex focusing lens | |
| LED | 1x OSRAM P8, CCT 6000-6500 K | Push switch (High/Off/Low/Off/Strobe/Off) | |
| Luminous intensity | Spot – High: 100 lm / 1225 cd Low: 8 lm Flood – High: 250 lm / 240 cd Low: 25 lm | Tactile operation when light on (Soft touch button when light on--High/Low/Strobe) | |
| Run Time | Low: 35 h High: 4 h Strobe: 2 h (VARTA Longlife battery required) | Reset to High mode if off longer than 20 s | |
| Range | 70 m | Twist head to focus beam (spot to flood or flood to spot) | |
| Material | Aluminium PC (Polycarbonate) Silicon Rubber (All contact parts made of nickel plated steel or stainless steel) | Broad and consistent flood beam with ultra view area | |
| Weight | 74.8 g (without batteries) | Comfortable handle with knurling pattern | |
| Dimensions | | Bracket clip removal function | |
| A | 164.1 mm | Eye risk group II | |
| B | 26 mm | 3.3 feet (1 m) drop test | |
| C | 19.5 mm | 10,000 switch cycle life | |
| D | 26.2 mm | | |

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries