



Designation:	18901 101 001
Battery Requirement:	1 x 18650 battery Li-Ion 3,7 V 2600 mAh 9.62 Wh
Lamp required:	1 pcs. CREE XPL HI LED, CCT5000K
Input:	DC 5V 500 – 2000 mA
Luminous intensity:	High mode: 700 lm Med mode: 200 lm Low mode: 30 lm
Beam distance:	High mode: 300 m Med mode: 188 m Low mode: 81 m
Weight:	359 g (without charger)
Material:	Aluminium PC (Polycarbonate) PMMA All contact parts made of bronze or nickel plated steel
Dimensions (mm):	A: 225.0 B: 37.9 C: 34.0
Run Time:	High mode: 2 h Med mode: 4 h Low mode: 24 h

- Features (Technical):**
- Charging circuit with protection for over-charged & over-discharged
 - Twist-Lock USB access via Tail Cap & Bracket clip removal function
 - MCU control multiple functions push switch (high/med/low/off), with 4 seconds memory wipe, double push- strobe/off; rechargeable flashlight and powerbank function
 - User display status discharging:
 - blue constant - full
 - blue blinking - intermediate
 - red blinking – low battery (remind when <10%)
 - Blue LED charging indicator: Flashes when charging<100%, solid ON when fully charged
 - Super bright Cree white LED
 - Type II anodized
 - 2 meter drop test
 - IPX 4 water resistant
 - Slide head to focus beam (spot to flood or flood to spot)
 - Broad and consistent flood beam with ultra view area
 - 10.000 switch cycle life
 - 10.000 micro USB plug insertion life test

No publication or circulation of data to third parties without consent of VARTA Consumer Batteries